

Direct Methanol Fuel Cells

Recent Advances in
Direct Methanol Fuel Cells
at Los Alamos National Laboratory

Xiaoming Ren, Sharon Thomas, Piotr Zelenay and
Shimshon Gottesfeld

Materials Science and Technology Division, LANL



Direct Methanol Fuel Cells

Outline

- *Programs & Projects*
 - DMFCs for Portable Power Sources (*DARPA*)
 - DMFCs for Potential Transportation Applications (*US DOE/OAAT*)
- *Technical -- Cells and Short Stacks*
 - POWER DENSITY
 - CROSSOVER AND FUEL UTILIZATION
 - COMMENTS ON ELECTROCATALYSIS



Direct Methanol Fuel Cells

DMFCs for Portable Power Sources

LANL Activities

(1) DMFC Core Technology Developments

- *Cell and stack component optimization
- *Target maximized performance (power & efficiency)
under the relevant operation conditions

(2) DMFC Stack technology

- * Develop DMFC stack generating 50W net power at ambient air pressure, near 60°C



Direct Methanol Fuel Cells

DMFCs for Portable Power Source

Recent Achievements

(1) MEA composition & fabrication optimized

(2) Optimized MEA & new DMFC hardware enable:

- *300W/l of active volume at 1 atm, 60°C

- *5-cell stack tested successfully (1000 hrs)

- *First introduction of 50W DMFC stack in 50W/150Wh system scheduled by end of '99

(* Completely passive DMFC of similar structure yielded recently 15 mW/cm² of MEA)



Direct Methanol Fuel Cells

DMFCs for Potential Transportation Applications

Objectives:

- **Develop DMFC materials, components and operation conditions to demonstrate the potential of DMFCs for transportation applications in terms of *power density, energy conversion efficiency and cost*:**
 - * optimize anode catalyst for performance & lower cost;**
 - * Prove low fuel utilization can be resolved with membranes of good conductivity and optimized stack operation conditions;**
 - * Prove stability of all cell components in longer term operation**



Direct Methanol Fuel Cells

DMFCs for Potential Transportation Applications

Achievements

- 5-cell LANL stack reconfigured to operate at 100°C , 30 psig air, generating **1 kW per liter** of active stack volume
- Fuel utilization near **90%** demonstrated in 5-cell DMFC stack near the expected design point of 0.50V
- This corresponds to overall conversion efficiency of **37%**
- Catalyst requirements lowered to **5 g Pt kW⁻¹ vs. about 2 g Pt kW⁻¹** estimated for today's on-board reforming system



Direct Methanol Fuel Cells

DMFCs for Potential Transportation Applications

Status

*In terms of *power density* and *energy conversion efficiency*, the DMFC (based on short stack results) is today *comparable with an on-board methanol reforming system*

(** Vehicle w. DMFC power system is considered ZEV)

* There is a remaining (*although smaller than perceived*) gap in precious metal catalyst requirements, with the DMFC requiring 5 g Pt kW⁻¹ vs. about 2 g Pt kW⁻¹ required today for an on-board reforming system



Direct Methanol Fuel Cells

DMFCs for Portable Power & Transportation Applications

Future Efforts

System Level Work with Present Technology:

Liquid feed DMFCs with “leaky membranes” need to be demonstrated at the *system level* with full resolution of efficiency and water management challenges

R&D:

Enhanced anode activity is key for elevating system efficiency over 37%. This can be achieved with either catalyst better than PtRu, strong improvement in anode catalyst layer structure and/or higher cell temperature

Less leaky membranes are of interest provided they maintain protonic conductivity of $0.1 \sigma / \text{cm}$



Acknowledgements

Work on DMFCs for Portable Power Applications
supported by:

Defense Advanced Research Projects Agency (DARPA)

Work on Polymer Electrolyte Fuel Cells & DMFCs
for Transportation Applications, supported by:

US DOE/Office of Advanced Automotive Technology

